

PMXTREME® ANSI • CE •



REVOLVER DE GOMA



INCLUYE CORREA



PUNTAS DE GOMA



OPCIÓN DE LECTURA

Boquilla de goma incorporada // Patillas flexibles ventiladas con puntas de goma // Incluye cordón de amarre negro // Impresión personalizada disponible



Montura negra con cordón | 11 Variaciones

- SB6310SP • Clear
- SB6310STP • Clear AF
- SB6320SP • Gray
- SB6320STP • Gray AF
- SB6330SP • Amber
- SB6345SP • Ice Orange Mirror
- SB6360SP • Infinity Blue
- SB6370SP • Silver Mirror
- SB6375SP • Blue Mirror
- SB6376SP • Smoke Green Mirror
- SB6380SP • I/O Mirror



SCM63



SR63



SS63

Montura de camuflaje con cordón | 3 Variaciones

- SCM6310STP • AF nítido
- SCM6318STP • Arenisca Bronce AF
- SCM6320STP • AF gris

Marco rojo con cordón | 1 Variación

- SR6320SP • Gris

Montura plateada con cordón | 2 Variaciones

- SS6310SP • Claro
- SS6365SP • Espejo Azul Hielo

PMXTREME LED ANSI • CE •



REVOLVER DE GOMA



PUNTAS DE GOMA



OPCIÓN DE LECTURA

Las bombillas LED giratorias súper brillantes (tres lúmenes por lado) le permiten ver en lugares oscuros mientras mantiene las manos libres // Revólver de goma incorporado y puntas de patillas de goma // Las pilas alcalinas proporcionan hasta 50 horas de uso antes de ser reemplazadas. Se incluyen tres pilas alcalinas L1154F (LR44) por patilla (seis en total) // Los interruptores de encendido/apagado de botón fáciles de usar están ubicados en la parte superior de cada patilla // Impresión personalizada disponible

Marco negro | 2 Variaciones

- SB6310SPLED • Claro
- SB6310STPLED • AF nítido



i Las baterías de repuesto no están disponibles.

PMXTREME Rx ANSI •



REVÓLVER DE GOMA

PUNTAS DE GOMA

Incluye inserto Rx que se adapta a lentes recetados de -3.0 a +3.0 // Lleve el inserto al optometrista local para la instalación de lentes Rx // Impresión personalizada disponible



Marco negro | 2 Variaciones

- SB6310STRX • AF nitido
- SB6320STRX • AF gris

Lectores PMXTREME® ANSI •



REVÓLVER DE GOMA

INCLUYE CORREA

PUNTAS DE GOMA

OPCIÓN DE LECTURA

Boquilla de goma incorporada // Patillas flexibles ventiladas con puntas de goma // Incluye cordón de amarre negro // Impresión personalizada disponible



Montura negra con cordón | 3 Variaciones

- SB6310SPR15 • Claro +1.5 Mag
- SB6310SPR20 • Claro +2.0 Maestría
- SB6310SPR25 • Claro +2.5 Mag

Lectores LED PMXTREME ANSI •



REVÓLVER DE GOMA

PUNTAS DE GOMA

OPCIÓN DE LECTURA

Las bombillas LED giratorias súper brillantes (tres lúmenes por lado) le permiten ver en lugares oscuros mientras mantiene las manos libres // Revólver de goma incorporado y puntas de patillas de goma // Las pilas alcalinas proporcionan hasta 50 horas de uso antes de ser reemplazadas. Tres pilas alcalinas L1154F (LR44) por patilla (seis en total) incluido // Los interruptores de encendido/apagado de botón fáciles de usar están ubicados en la parte superior de cada patilla

Marco negro | 3 Variaciones

- SB6310STPLEDR15 • AF nitido +1.5 Mag
- SB6310STPLEDR20 • AF nitido +2.0 Maestría
- SB6310STPLEDR25 • AF nitido +2.5 Mag



i Las baterías de repuesto no están disponibles.

PMXTREME®

Especificaciones generales

Peso: 27 g
 PD: 72 mm
 Puente: 14 mm
 Base de la lente: 9 curvas
 Tamaño de la lente en diagonal: 78 mm
 Tamaño de la lente vertical: 46 mm
 Grosor de la lente: 2,3 mm
 Longitud total (lente - punta): 103 mm
 Ancho total (bisagra - bisagra): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Temple tips: rubber
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber

Part No.	Lens Marking	Temple Marking
SB6310SP	P + U6	P Z87 +
SB6310STP	P + U6	P Z87 +
SB6320SP	P + U6 L3	P Z87 +
SB6320STP	P + U6 L3	P Z87 +
SB6330SP	P + U6	P Z87 +
SB6345SP	P + L3	P Z87 +
SB6360SP	P + U6 L1.3	P Z87 +
SB6370SP	P + L3	P Z87 +
SB6375SP	P + L3	P Z87 +
SB6376SP	P + L3	P Z87 +
SB6380SP	P + U6 L1.7	P Z87 +
SCM6310STP	P + U6	P Z87 +
SCM6318STP	P + U6 L2.5	P Z87 +
SCM6320STP	P + U6 L3	P Z87 +
SR6320SP	P + U6 L3	P Z87 +
SS6310SP	P + U6	P Z87 +
SS6365SP	P + L3	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light
 L3: 18% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

PMXTREME LED

General Specifications

Weight: 50 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Temple tips: rubber
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber

Nº de pieza	Marcado de lentes	Marcaje de las patillas
SB6310SPLED	P + U6	P Z87 +
SB6310STPLED	P + U6	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

PMXTREME Rx

General Specifications

Weight: 29 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 146 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Temple tips: rubber
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber
 Rx Insert: thermoplastic

Part No.	Lens Marking	Temple Marking
SB6310STRX	P + U6	P Z87 +
SB6320STRX	P + U6 L3	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L3: 18% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

Lectores PMXTREME®

General Specifications

Weight: 27 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Temple tips: rubber
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber

Part No.	Lens Marking	Temple Marking
SB6310SPR15	P + U6	+1.50 P Z87 +
SB6310SPR20	P + U6	+2.00 P Z87 +
SB6310SPR25	P + U6	+2.50 P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

Lectores LED PMXTREME®

General Specifications

Weight: 50 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Temple tips: rubber
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber

Part No.	Lens Marking	Temple Marking
SB6310STPLEDR15	P + U6	+1.50 P Z87 +
SB6310STPLEDR20	P + U6	+2.00 P Z87 +
SB6310STPLEDR25	P + U6	+2.50 P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact