

Fanvil X4/X4G Enterprise IP Phone

The new Fanvil X4 IP Phone is an enterprise desktop phone which comes with an intelligent DSS Key-mapping LCD to increase enterprise users' work efficiency at a cost-effective price.

Highlights

- ✓ DSS Key-mapping LCD – 6 DSS keys corresponded to the LCD display to provide dynamic DSS/BLF functions up to five pages at virtualized total 30 DSS keys.
- ✓ Fast / Gigabit Ethernet – 10/100Mbps or 10/100/1000Mbps Ethernet with POE enabled.
- ✓ Economic and Environmentally Friendly design with elegant housing.



Model	Screen	Network	POE	Power adapter
X4	2.8" color-screen	10/100Mbps	√	×
X4G	2.8" color-screen	10/100/1000Mbps	√	×

Generic

- 4 SIP Lines
- HD Voice
- POE Enabled
- 2 LCDs (Main + DSS)
- Handset / Hands-free / Headset mode
- Intelligent DSS Keys
- Desktop / Wall-mount installation
- Optional External Power Supply

Call Features

- Call out / Answer / Reject
- Mute / Unmute (microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (depending on server)
- Redial/Auto-Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (on server)
- 3-way Conference
- Hot Line
- Hot desking

Phone Features

- Local Phonebook (500 entries)
- Remote Phonebook (XML/LDAP, 500 entries)
- Call logs (in/out/missed, 600 entries)
- Blocked list/Allowed list
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Support Poly headset
- Support Jabra wireless headset (Through Fanvil EHS20 EHS Cable)
- Support Recording (Through Server Recording)
- Action URL / Active URI
- uaCSTA

Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0~7KHz Frequency Response)
- Wideband ADC/DAC16KHz Sampling
- Narrowband CODEC: G.711a/u, G.723.1, G.726-32, G.729AB
- Wideband CODEC: G.722
- Full-duplex Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band – DTMF-Relay(RFC2833) / SIP INFO

Networking

- Physical: 10/100Mbps(X4), 10/100/1000Mbps(X4G) Ethernet, dual bridged port for PC bypass



- IP Configuration: Static / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- LLDP
- QoS
- RTCP-XR(RFC3611), VQ-RTCPXR(RFC6035)

Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- PPPoE
- LLDP
- 802.1x
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

Deployment & Maintenance

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCPOPT66/SIP PnP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog

Physical Specifications

- Main LCD x1: 2.8 inch (320x240) color-screen LCD

- DSS Key-mapping LCD x1: 2.4 inch (320x240) color-screen LCD
- Keypad: 38 keys, including
 - 4 Soft-keys
 - 6 Function keys (Hold, Call forward, Conference, Phonebook, Call logs, Redial)
 - 4 Navigation keys
 - 1 OK key
 - 12 Standard Phone Digits keys
 - 3 Volume Control keys, Up/Down/Mute(Microphone)
 - 1 Hands-free key
 - 6 DSS Keys with tri-color LED
 - 1 Page-Jump/Configuration (PIC) key
- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT5 Ethernet Cable x1
- Back Rack x1
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- DC Power Input: 5V/600mA(X4), 5V/1A(X4G)
- Power Consumption (X4): Idle 1.2W~1.9W, Peak 2.4W~3.5W
- Power Consumption (X4G): Idle 1.8W~2.5W, Peak 3W~4.5W
- Working Temperature: 0~40°C
- Working Humidity: 10~95%
- Qty/CTN:10pcs
- N.W/CTN: 10.38kg
- G.W/CTN: 11.1kg
- Installation: Desktop Stand or Wall-mount
- Color: Black
- Device Dimensions:
 - Desktop Stand (angles 1): 196x169x172mm
 - Desktop Stand (angles 2): 196x185.7x153mm
 - Wall-mount: 196x102.9x218mm
- Gift Box Dimensions: 270x270x65mm
- Outer CTN Dimensions: 555x340x290mm (10 PCS)

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products. Customers should consult Fanvil's retailers, distributors, or Fanvil directly, if customers have concerns on any feature.

For more information, please visit: www.fanvil.com

